

Carbon Monoxide Alarm – Ei3018



- Contains our proven Electrochemical CO sensor
- Mains powered with 10 year rechargeable Lithium cell back-up
- Compatible with SmartLINK® interconnection and monitoring technology
- AudioLINK™ Data extraction technology
- *easi-fit* base
- 10 year life

CONTAINS:



FOR WIRELESS INTERCONNECTION:

ADD Ei3000MRF



PRODUCT DESCRIPTION

The Ei3018 is a Carbon Monoxide (CO) Alarm powered by 230V AC mains power, and has built in tamper proof rechargeable lithium cells that act as a battery back up in the event of mains failure. These rechargeable lithium cells are designed to last the life of the CO alarm.

The Ei3018 has a high performance, proven electrochemical sensor (10 year life) to sense CO presence. The sensor is individually calibrated and tested in CO gas to ensure accuracy. In alarm, the flash rate of the red LED indicates the level of CO detected.

The Ei3018 contains AudioLINK technology, which allows you to extract real time data from the alarm directly to a smartphone or tablet via the AudioLINK App.

The Ei3018 can operate as a standalone alarm or can be interconnected either by hard-wire or wirelessly (using the Ei3000MRF module) enabling it to communicate with compatible alarms and accessories. Up to 12 devices can be interconnected.


The memory feature allows an alarm that has previously activated to be easily identified (through the red flashing LED).

The alarm is fitted with a large Test/ Silence button to facilitate frequent testing of the alarm and system. The silence function allows the alarm/system to be silenced in the case of a false/ nuisance alarms and low battery/ fault beeps.

SmartLINK compatible - plug in an Ei3000MRF module for wireless interconnection, data extraction and real-time notifications of alarm activations and events via the SmartLINK Gateway and Portal.

TECHNICAL SPECIFICATION

- Sensor Type:** Electrochemical Cell
- Supply Voltage:** 230V AC, 50 Hz
- Power Consumption:** 0.25W (standby)
- Battery back-up:** Rechargeable lithium cells
- Alarm Horn:** Piezoelectric
- Sound Level:** 85 dB(A) at 3 metres
- Button Test:** Checks sensor, electronics and sounder
- Silence Function:** Silences alarm for 10 minutes
Silences fault beeps for 12 hours
- AudioLINK:** Enabled
- SmartLINK:** Compatible via the Ei3000MRF module
- Indicator Lights:** **Green** - Power
Red - Pre-alarm/ Alarm/ Silence mode/ Memory
Yellow - Fault/ End of life
- Memory Feature:** Records last alarm event
- Fixing:** *easi-fit* base (supplied)
- Temperature:** Operating 0°C to 35°C
- Humidity Range:** 15% to 95% RH (non condensing)
- Plastic material:** HIP UL 94 V0 Flame Retardant
- Dimensions:** Product - 150mm x 55mm
Package - 180mm x 155mm x 62mm
- Weight:** 310g (Boxed 376g)
- Warranty:** 5 year (limited) warranty
- Approvals:**



Specifications are subject to change

Rev0 03/2018 LJD

www.aico.co.uk

Tel: 01691 664100

e-mail: enquiries@aico.co.uk



Aico Ltd. Mile End Business Park, Maesbury Road, Oswestry, Shropshire, SY10 8NN

Company Registration No. 2544399
WEEE Registration No. WEE/AE0109WY
Battery Producer Registration No. 2544399w