

Standard Call Push with Protruding Button, No Reset, No Remote

Part No. **NC917L**



Overview

- A standard call point c/w protruding button for use with C-TEC's 800 Series Call System.
- Red reassurance LED confirms a call has been made.
- Requires a separate reset point for cancelling calls.
- Mounts on a standard UK 25mm single gang flush or surface back box.



More Information

Technical Specifications

Quiescent current	0mA.
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Red Reassurance LED (lit constant for Standard calls).
Controls	Red protruding call button (generates a Standard call when pressed). An additional 800 Series device with a reset function is required to reset this device.
Connections	SIG (Signal); -Ve (Negative).
Onboard Sounder	No.
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 32 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	62g.



Operating conditions/temperature -5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom