

CO-9XT-FF BATTERY POWERED CO ALARM

Sensor type	Advanced electrochemical
Battery type	7 year sealed for life lithium



- Advanced electrochemical sensor - calibrated and tested in CO gas.
- 7 year sealed for life lithium battery.
- Alarm can be free-standing or wall mounted.
- Supplied with tamper resistant Fast-Fit bracket with single pin or 2 screw fitting options.
- Test button - to test circuitry and sounder.



BS EN 50291-1:2010
BS EN 50291-2: 2010
Licence No: KM 551504



Technical Specification

Dimensions	112mm (width) x 72mm (height) x 35mm (depth)	
Supply voltage	3V DC	
Battery back-up	7 year sealed for life lithium battery	
Technology	Advanced electrochemical	
Alarm sound level	85dB(A) at 1m (minimum)	
Installation positions	Wall / Free-standing	
Operating temperature	-10° C to +40° C	
Operating humidity	30% to 90% RH non-condensing	
Storage temperature	-20° C to +60° C	
Storage humidity	Up to 93% RH non-condensing	
Plastic material	ABS, UL94 VO fire retardant	
Warranty	7 years	
Master pack quantity	20	
Weight	106g	
Certified to	BS EN 50291-1 & 2: 2010	
Independently tested to	N/A	
Maximum number of connected units	N/A	
Operating Frequency	N/A	
Range	N/A	